



# Release Notes for Cisco FindIT Network Discovery Utility, Version 2.0.5

---

**First Published:** 2017-09-20

**Last Modified:** 2020-08-19

## Introduction

These release notes describe the recommended practices and known issues that apply to software version 2.0.5 of Cisco FindIT Network Discovery Utility.

## What's New in Cisco FindIT, Release 2.0.5

The following changes have been made in Cisco FindIT Network Discovery Utility version 2.0.5:

- Updates to maintain interoperability with Cisco software and support services
- Fixes a problem discovering devices when running on Microsoft Windows
- The FindIT extension for the Apple Safari web browser is no longer available

## System Requirements for Cisco FindIT Network Discovery Utility

Your PC must meet the following requirements to run Cisco FindIT.

- Operating system:
  - Microsoft Windows 7, 8, 8.1 or 10
  - Apple OS X 10.15 or above
- Web browser
  - Google Chrome version 84 or above
  - Microsoft Internet Explorer version 10 or above
  - Mozilla Firefox 80 or above
- Your network devices must meet the following requirements to be monitored and accessed through Cisco FindIT.
  - Must be on the same subnet as the PC that is running Cisco FindIT.
  - Must be a Cisco Small Business device with the Bonjour service supported and enabled (see the Administration Guide or Online Help for the device).

**REVIEW DRAFT - CISCO CONFIDENTIAL**

**Limitations and Restrictions**

Be aware of the following issues when using Cisco FindIT to monitor and manage the network:

<b>Problem</b>	<b>Solution</b>
If the master access point in a Single Point Setup cluster is removed from the cluster, FindIT will not automatically update the device tree. (CSCuy00810)	Manually refresh the device tree
In rare circumstances, the device tree can take up to a minute to accurately reflect changes to Single Point Setup cluster membership. The member count may also be incorrect. (CSCuy00820)	Manually refresh the device tree
If HTTPS access to the administration Graphical User Interface (GUI) of a device is disabled, it may take up to two minutes before FindIT will connect using HTTP when double-clicking on the device in the Discovery view. Within those two minutes, the browser will report the administration GUI as being unreachable. (CSCut68745)	Wait for two minutes after disabling HTTPS before using FindIT to connect to the administration GUI; you may also manually enter the HTTP URL into the address bar of the browser using the IP address visible in the device information tooltip.

**Where to Find Support**

For current support information, visit the following URLs:

*Table 1: Where to Find Support*

<b>Support</b>	
Cisco FindIT Network Management Support Forums	<a href="https://supportforums.cisco.com/t5/findit-network-management/ct-p/2116-findit">https://supportforums.cisco.com/t5/findit-network-management/ct-p/2116-findit</a>
Phone Support Contacts	<a href="http://www.cisco.com/go/sbse">http://www.cisco.com/go/sbse</a>
<b>Product Documentation</b>	
Cisco FindIT Network Management Support and Documentation Resources	<a href="http://www.cisco.com/c/en/us/support/cloud-systems-management/findit-network-management/tsd-products-support-series-home.html">http://www.cisco.com/c/en/us/support/cloud-systems-management/findit-network-management/tsd-products-support-series-home.html</a>
<b>Cisco Small Business</b>	
Cisco Small Business Home	<a href="http://www.cisco.com/go/smb">http://www.cisco.com/go/smb</a>
Cisco Small Business Support Community	<a href="http://www.cisco.com/go/smallbizsupport">http://www.cisco.com/go/smallbizsupport</a>

