



SIP: RFC 2782 Compliance with DNS SRV Queries

- [Overview, on page 1](#)
- [SIP RFC 2782 Compliance with DNS SRV Queries, on page 2](#)
- [Configure DNS Server Lookups , on page 3](#)
- [Verifying, on page 4](#)

Overview

Effective with Cisco IOS XE Release 2.5, the Domain Name System Server (DNS SRV) query used to determine the IP address of the user endpoint is modified in compliance with RFC 2782 (which supersedes RFC 2052). The DNS SRV query prepends the protocol label with an underscore "_" character to reduce the risk of duplicate names being used for unrelated purposes. The form compliant with RFC 2782 is the default style.

Feature Information

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for SIP: RFC 2782 Compliance with DNS SRV Queries

Feature Name	Releases	Feature Information
SIP: RFC 2782 Compliance of DNS SRV Queries	Cisco IOS XE Release 2.5	Effective with Cisco IOS XE Release 2.5, the DNS SRV query used to determine the IP address of the user endpoint is modified in compliance with RFC 2782 (which supersedes RFC 2052). The DNS SRV query prepends the protocol label with an underscore "_" character to reduce the risk of duplicate names being used for unrelated purposes. The form compliant with RFC 2782 is the default style. The following command was introduced or modified: srv version .

SIP RFC 2782 Compliance with DNS SRV Queries

Session Initiation Protocol (SIP) on Cisco VoIP gateways uses the DNS SRV query to determine the IP address of the user endpoint. The query string has a prefix in the form of "protocol.transport." and is attached to the fully qualified domain name (FQDN) of the next hop SIP server. This prefix style originated in RFC 2052. Beginning with Cisco IOS XE Release 2.5, a second style, in compliance with RFC 2782, prepends the protocol label with an underscore "_"; for example, "_protocol._transport." The addition of the underscore reduces the risk of the same name being used for unrelated purposes. The form compliant with RFC 2782 is the default style.



Note The DNS SRV lookup is always attempted first for a Fully Qualified Domain Name (FQDN). If the DNS SRV lookup fails CUBE falls back to A-AAAA lookup. If you manually add a port number to a FQDN, the CUBE performs an A-AAAA lookup instead of SRV lookup.

Example:

'session target dns:cisco.com' would perform an SRV lookup and 'session target dns:cisco.com:5060' would perform an A-AAAA lookup.

Configure DNS Server Query Format RFC 2782 Compliance with DNS SRV Queries

Compliance with RFC 2782 changes the DNS SVR protocol label style. RFC 2782 updates RFC 2052 by prepending the protocol label with an underscore character. The prefix format compliant with RFC 2782 is the default format. However, backward compatibility is available, allowing newer versions of Cisco IOS software to work with older networks that support only RFC 2052 DNS SVR prefix style.

To configure the format of DNS SRV queries to comply with RFC 2782, complete this task.



Note You do not have to perform this task if you want to use the default RFC 2782 format.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **interface** *type number*
4. **sip-ua**
5. **srv version** {1 | 2}
6. **exit**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode.

	Command or Action	Purpose
	Example: <pre>Router> enable</pre>	<ul style="list-style-type: none"> Enter your password if prompted.
Step 2	configure terminal Example: <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3	interface type number Example: <pre>Router(config)# interface gigabitethernet 0/0/0</pre>	Configures an interface type and enters interface configuration mode
Step 4	sip-ua Example: <pre>Router(config-if)# sip-ua</pre>	Enters SIP UA configuration mode.
Step 5	srv version {1 2} Example: <pre>Router(config-sip-ua)# srv version 2</pre>	Generates DNS SRV queries in either RFC 2782 or RFC 2052 format. <ul style="list-style-type: none"> 1 --The query is set to the domain name prefix of protocol.transport. (RFC 2052 style). 2 --The query is set to the domain name prefix of _protocol._transport. (RFC 2782 style). This is the default.
Step 6	exit Example: <pre>Router(config-sip-ua)# exit</pre>	Exits the current configuration mode.

Configure DNS Server Lookups

Following is the example to configure '_sip_udp.'

```
!
dial-peer voice 1 voip
  session protocol sipv2
  session transport udp
  session target dns:cisco.com
!
```

Following are the examples to configure '_sip_tcp.'

```
!
dial-peer voice 1 voip
  session protocol sipv2
  session transport tcp
```

```

    session target dns:cisco.com
  !
  !
dial-peer voice 1 voip
  session protocol sipv2
  session transport tcp tls
  session target dns:cisco.com
  !

```

Following is the example to configure '_sips._tcp.'.

```

  !
dial-peer voice 1 voip
  session protocol sipv2
  session transport tcp tls
  session target dns:cisco.com
  voice-class sip url sips
  !

```

From Cisco IOS XE Release 16.12.3 onwards, CUBE sends '_sips._tcp.' query when the transport is TLS. The '_sips._tcp.' query is independent of the URI scheme—sip or sips. Following is the example to configure '_sips._tcp.'.

```

  !
dial-peer voice 1 voip
  session protocol sipv2
  session transport tcp tls
  session target dns:cisco.com
  !

```

Following is the sample configuration for a local DNS SRV.

```

  !
ip name-server 172.18.110.64
  !
ip domain lookup
  !
ip host 1.cisco.com 10.10.10.1
ip host 2.cisco.com 10.10.10.2
ip host 3.cisco.com 10.10.10.3
  !
ip host _sip._tcp.cisco.com srv 1 50 5061 1.cisco.com
ip host _sip._tcp.cisco.com srv 1 50 5061 2.cisco.com
ip host _sip._tcp.cisco.com srv 1 50 5061 3.cisco.com
  !
ip host _sips._tcp.cisco.com srv 1 50 5061 1.cisco.com
ip host _sips._tcp.cisco.com srv 1 50 5061 2.cisco.com
ip host _sips._tcp.cisco.com srv 1 50 5061 3.cisco.com
  !
ip host _sip._udp.cisco.com srv 1 50 5060 1.cisco.com
ip host _sip._udp.cisco.com srv 1 50 5060 2.cisco.com
ip host _sip._udp.cisco.com srv 1 50 5060 3.cisco.com
  !
ip host _sip._tcp.cisco.com srv 1 50 5060 1.cisco.com
ip host _sip._tcp.cisco.com srv 1 50 5060 2.cisco.com
ip host _sip._tcp.cisco.com srv 1 50 5060 3.cisco.com
  !

```

Verifying

The following example shows sample is output from the **show sip-ua status** command used to verify the style of DNS server queries:

```
Router# show sip-ua status
SIP User Agent Status
SIP User Agent for UDP : ENABLED
SIP User Agent for TCP : ENABLED
SIP User Agent bind status(signaling): DISABLED
SIP User Agent bind status(media): DISABLED
SIP max-forwards : 6
SIP DNS SRV version: 1 (rfc 2052)
```

