



## Release Notes for SONiC on Cisco 8000 Series Routers, Release 202205.2.x

[SONiC on Cisco 8000 Series Routers, Release 202205.2.x](#) 2

[Component Version](#) 2

[Tier 1 Baseline Features](#) 3

[What's New in the Release](#) 5

[Software Download](#) 6

[Related Documentation](#) 6

Revised: November 29, 2023

# SONiC on Cisco 8000 Series Routers, Release 202205.2.x

Cisco 8000 series routers support disaggregating the hardware and software to provide a more robust, open ecosystem for service provider networks.

With the introduction of Open Compute Project (OCP), vendors collaborate on designs and specifications to enable a more efficient, scalable, and versatile consumption of hardware and software. This initiative broadens the spectrum for cloud and service provider transformations, hardware innovations, software evolutions, flexibility, lower costs, and better control of the network infrastructure.

As part of the disaggregation journey, Cisco supports installing Software for Open Networking in the Cloud (SONiC) on the following PIDs on the Cisco 8000 series routers:

Product ID (PID)	Description
8101-32FH-O	Cisco 8100 1 RU Chassis with 32x400G QSFP56-DD with Open Software and without HBM on Q200 Silicon
8102-64H-O	Cisco 8100 2 RU Chassis with 64x100G QSFP28 with Open Software and without HBM on Q200 Silicon

SONiC is an open source network operating system based on Linux that runs on switches from multiple vendors and ASICs. SONiC offers a full-suite of network functionality, like BGP and RDMA, that has been production-hardened in the data centers of some of the largest cloud-service providers. Cisco is part of this ecosystem harnessing the innovation in Cisco Silicon One to provide seamless infrastructure experience in data center deployments. Cisco Silicon One devices can assign ports to be generic Ethernet or a fully scheduled fabric. The Cisco Silicon One architecture enables optimized fixed form factor systems. Cisco leverages the SONiC capabilities from the community for a deployment-hardened network stack on the Cisco 8000 series routers.

SONiC uses Switch Abstraction Interface (SAI) API version 1.10.2 for release 202205. The SAI API defines the API to provide a mechanism to control forwarding elements, such as a switching ASIC, an NPU or a software switch in a uniform manner. For more information about SAI APIs, refer the [Github](#) repository.

For more information about the benefits of integrated innovation, see [Cisco 8000 series routers](#).

## Component Version

Feature	Version
Linux kernel	5.10.0-18-2 (5.10.140-1)
SAI API	1.10.2
FRR	8.2.2
LLDPD	1.0.4-1
TeamD	1.30-1
SNMPD	5.9+dfsg-4+deb11u1
Python	3.9.2-1

Feature	Version
SYNCD	1.0.0
swss	1.0.0
Radvd	1:2.18-3
Isc-dhcp	4.4.1-2
sonic-telemetry	0.1
redis-server/ redis-tools	5:6.0.16-1+deb11u2

## Tier 1 Baseline Features

The following list provides common Tier 1 (T1) baseline features supported on SONiC:

- TACACS+ authentication for IPv4 or IPv6 addresses
- SSHv2 authentication for IPv4 or IPv6 addresses
- AAA authentication
- Syslog logging for IPv4 or IPv6 addresses
- Network Time Protocol (NTP) for IPv4 or IPv6 addresses
- Simple Network Management Protocol (SNMP) over IPv4 and IPv6 transport
- TFTP file transfers over IPv4 or IPv6 addresses
- Secure Copy (SCP) server support
- Dynamic Host Configuration Protocol (DHCP) relay agent
- Access Control Lists (ACLs) over IPv4 and IPv6 addresses
- IPv4 or IPv6 ACL match on 7 tuple
- ERSPAN and Everflow Support
  - Source interface to support IPv4 capture and IPv6 capture at the same time
  - Bit-wise match on DSCP
  - Capture IPv4 and IPv6 source packets and encapsulation with either IPv4 or IPv6 addresses
- IPv4 or IPv6 decapsulation
- IPv4 or IPv6 routing
- Static route
- iBGP over IPv4 or IPv6 addresses
- eBGP over IPv4 or IPv6 addresses

- Route policies
- IP prefix lists
- BGP
  - Multihop, AS-set, prefix-set, community-list
  - Max prefix limit
  - Bestpath as-path multipath-relax
  - Soft reconfiguration
  - Update source loopback
- 32-way ECMP
- LAG: IPv4 or IPv6 interfaces addresses
- LACP Support
- RDMA: QOS-RDMA and QOS-ECN
- MTU: Jumbo MTU 9100 for Management, Switched Virtual Interface (SVI) and Native interfaces
- SNMP: Trap source management interface in the management VRF
- COPP/LPTS: For both management and inband interfaces (v4 or v6 UMPP)
- NTP:
  - Support of IPv4 or IPv6 Servers
  - Access-group server ACL
- Security ACL:
  - SSH IPv4 and IPv6 access
  - Physical interfaces—IPv4 and IPv6 ACL support
  - ACL permit, deny actions or counters
- ACL
 

Match conditions:

  - 5-tuple match for an ACL (source and destination IP, source and destination port and protocol type)
  - port range
- QoS classification and scheduling over IPv4 or IPv6 addresses
- Syslog support
- gRPC: Dial-out support to stream telemetry data

## What's New in the Release

The following features are introduced or enhanced in this release:

### 202205.2.4

The following features are introduced or enhanced in this release:

- Support for automatic FPD upgrade
- Display status of power supply LEDs using **show platform psustatus** command
- IOFPGA fix to bring up the optics port in low power mode
- Fix Ordered Equal Cost Multi-Path (ECMP) next hop group (NHG) drop when a route is added before the members are added to the group
- Resolve port handling of empty ECMP group to drop packets

### 202205.2.3

The following features are introduced or enhanced in this release:

- Quality enhancements for platform infrastructure and forwarding features
- Zero Touch Provisioning (ZTP) on 8101-32FH-O PID
- Enable Configuration Management Information Service (CMIS ) to allow integration with various network management tools, automation frameworks, and orchestration systems on 8101-32FH-O PID
- Enable sub port to configure static breakout that allows a high-speed port to be divided into multiple lower-speed ports, effectively increasing the number of available ports on the router on 8101-32FH-O PID
- Upgrade Field-Programmable Gate Arrays (FPGA) devices
- Fix to move control packets from queue 0 to queue 7
- Fix for Equal-Cost Multi-Path (ECMP) routing across all port-channels for IPinIP packets
- Field-Programmable Device (FPD) upgrade to version 1.88 on 8102-64H-O and version 1.89 on 8101-32FH-O PIDs
- 9100 Tag Protocol Identifier (TPID) to identify the protocol encapsulated within the Ethernet frame in a specific fanout configuration

### 202205.2.2

The following features are introduced or enhanced in this release:

- Quality enhancements in platform infrastructure and forwarding features.
- Support for the hardware SKUs (port configurations)—Cisco-8101-O32, Cisco-8101-O8C48 and Cisco-8101-C64.

### 202205.2.1

The following features are introduced or enhanced in this release:

- Quality enhancements in platform infrastructure and forwarding features.
- RDMA support on 8101-32FH-O PID.
- Serviceability: Enhancements for BFD. For more information, see [Serviceability](#).

## Software Download

Download the SONiC image from the [Cisco Software Download Center](#).

## Related Documentation

Refer the following pages for more information about SONiC on Cisco 8000 Series Routers:

- [Explore SONiC on Cisco 8000 Series Routers](#)
  - [Install SONiC on Cisco 8000 Series Routers](#)
  - [Setup SONiC on Cisco 8000 Series Routers](#)
  - [Network Scenario: 3-Stage Clos Network with Static VXLAN](#)
  - [Serviceability](#)
- [Cisco 8000 Series Routers Data Sheet](#)





**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA 95134-1706  
USA

**Asia Pacific Headquarters**  
CiscoSystems(USA)Pte.Ltd.  
Singapore

**Europe Headquarters**  
CiscoSystemsInternationalBV  
Amsterdam,TheNetherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).