



## **Compatibility Matrix for Cisco Unified Communications Manager and the IM and Presence Service, Release 12.5(X)**

[Compatibility Matrix for Cisco Unified Communications Manager and the IM and Presence Service](#) 2

[Revision History](#) 2

[Purpose of this Document](#) 3

[Supported Upgrade and Migration Paths](#) 4

[Supported Versions](#) 6

[Unified Communications Manager Compatibility Information](#) 8

[IM and Presence Service Compatibility Information](#) 25

Revised: August 31, 2023

# Compatibility Matrix for Cisco Unified Communications Manager and the IM and Presence Service

## Revision History

Date	Revision
August 30, 2023	Initial release version for 12.5(1)SU8a.
August 30, 2023	Updated support version for Unified CM Release 12.5(1)SU8a.
August 03, 2023	Initial release version for 12.5(1)SU8.
August 03, 2023	Updated support versions for 12.5(1)SU8.
August 03, 2023	Added support for Cisco Video Phone 8875 and Cisco Video Phone 8875NR.
January 31, 2023	Initial release version for 12.5(1)SU7a.
January 31, 2023	Updated support version for Unified CM Release 12.5(1)SU7a.
November 29, 2022	Initial release version for 12.5(1)SU7.
December 08, 2022	Updated upgrade paths and version support for 12.5(1)SU7.
December 08, 2022	Webex Desk Camera is rebranded to Cisco Desk Camera 4K.
December 08, 2022	Added support for Cisco Desk Camera 1080p.
December 08, 2022	Added support for Cisco Headset 320 Series and Cisco Headset 720 Series.
February 15, 2022	Initial release version for 12.5(1)SU6.
February 15, 2022	Updated upgrade paths and version support for 12.5(1)SU6.
February 15, 2022	Added support for Webex Desk Hub and Webex Wireless Phone 800 Series
May 05, 2022	Renamed some of the ROOM device names to remove Webex from them.
August 03, 2021	Initial release version for 12.5(1)SU5.
August 03, 2021	Updated upgrade paths and version support for 12.5(1)SU5.
August 03, 2021	Added Microsoft Exchange Server 2019 support for the IM and Presence Service Calendar Integration with Microsoft Outlook.
February 22, 2021	Initial release version for 12.5(1)SU4.
February 22, 2021	Updated upgrade paths and version support for 12.5(1)SU4.

<b>Date</b>	<b>Revision</b>
February 22, 2021	Added IM and Presence Service support for the advertisement of XMPP stream features/services over Mobile and Remote Access.
February 22, 2021	Added support for Cisco VG420 Analog Voice Gateway and Cisco Catalyst 8300 Series Edge Platforms.
March 25, 2021	Fixed the 7941 G Series EOS URL.
April 28, 2021	Added support for Ciphers for Application and OS End Users.
August 13, 2020	Updated version support for 12.5(1)SU3.
August 13, 2020	Added support for Microsoft® Active Directory® Federation Services 3.0, 4.0, and 5.0, and Microsoft Azure.
October 19, 2020	Corrected list of Webex endpoints.
November 18, 2020	Corrected dates.
December 13, 2020	Renamed Cisco Webex Teams to Cisco Webex.
June 19, 2019	Added OpenJDK version for 12.5(1)SU1 release.
	Updated for 12.5(1)SU1. Changed title to 12.5(x)
February 03, 2020	Updated upgrade paths, LDAP support, version support for 12.5(1)SU2.
February 20, 2020	Updated LDAPv3 Compliant Directories.
March 09, 2020	Updated Cisco Endpoint Support section.
March 11, 2020	Added Cisco Headsets to Endpoint Support.
April 06, 2020	Removed non-supported Cisco endpoints.
May 12, 2020	Added JTAPI Support information.
July 8, 2020	Updated SSL Connections and SSH Clients.
July 27, 2020	Updated supported ciphers list for IM and Presence Service.

## Purpose of this Document

This document contains compatibility information for 12.5(x) releases of Cisco Unified Communications Manager (Unified Communications Manager) and the Cisco Unified Communications Manager IM and Presence Service (IM and Presence Service). This includes subsequent SU releases as well, unless indicated otherwise.

## Supported Upgrade and Migration Paths

The following table highlights supported upgrade paths to upgrade to 12.5(x) releases of Unified Communications Manager and the IM and Presence Service.



**Note** Unless indicated otherwise, each release category includes the SU releases within that category. For example, 12.5(x) includes 12.5(1)SU releases. In addition, releases like 10.5(x) and 11.x include any SU releases within those categories as well.

**Table 1: Supported Upgrade Paths for Cisco Unified Communications Manager and the IM and Presence Service**

Source	Destination	Supported Upgrade Method	Version Switching* (Source to Destination and Vice Versa)
<b>Cisco Unified Communications Manager Upgrade Paths</b>			
Unified CM 10.0(x)	12.5(x)	PCD Migration**	Version switching not supported
Unified CM 10.5(x), 11.x, 12.0(x)	12.5(x)	Unified OS Admin upgrade (direct refresh) CLI upgrade (direct refresh) PCD Upgrade (direct refresh)** PCD Migration** Fresh Install with Data Import only to destination 12.5(1)SU5 or later. <b>Note</b> <ul style="list-style-type: none"> <li>• If the source release is 10.5(x) and the destination release is 12.5(1) through 12.5(1)SU5, PCD Upgrade Task is supported.</li> <li>• If the source release is 10.5(x) and the destination release is 12.5(1)SU6 and above, PCD Upgrade Task is not supported.</li> </ul>	Version switching supported for upgrades, but not for migrations
Unified CM 12.5(x)	12.5(y)	Unified OS Admin upgrade (direct standard) CLI upgrade (direct standard) PCD Upgrade (direct standard)** Fresh Install with Data Import only to destination 12.5(1)SU5 or later.	Version switching supported for upgrades, but not for migrations
<b>IM and Presence Service Upgrade Paths</b>			
IM and Presence 10.0(x)	IM and Presence 12.5(x)	PCD Migration**	Version switching not supported

Source	Destination	Supported Upgrade Method	Version Switching* (Source to Destination and Vice Versa)
IM and Presence 10.5(x), 11.x or 12.0(x)	12.5(x)	Unified OS Admin upgrade (direct refresh) CLI upgrade (direct refresh) PCD upgrade (direct refresh)** PCD Migration** Fresh Install with Data Import only to destination 12.5(1)SU5 or later.	Version switching supported for upgrades, but not supported for migrations.
IM and Presence 12.5(x)	12.5(y)	Unified OS Admin upgrade (direct standard) CLI upgrade (direct standard) PCD upgrade (direct standard)** Fresh Install with Data Import only to destination 12.5(1)SU5 or later.	Version switching supported for upgrades, but not supported for migrations.

\* Version switching refers to the ability to install the new version as an inactive version and switch to the new version, and revert to the old version, whenever you want. This capability is supported with most direct upgrades, but not with migrations.

\*\* PCD Upgrades and Migrations—Use Cisco Prime Collaboration Deployment Release 12.6 or later for all PCD tasks. If you want to upgrade or migrate to Unified CM Release 12.5(1)SU6 and above, ensure that you use the Release 14 version of the Cisco Prime Collaboration Deployment.

## Required COP Files

The tables below lists the upgrade paths that require COP files. You must install COP files on each node before you begin an upgrade using the Cisco Unified OS Administration interface, or before you begin an upgrade or migration using the Prime Collaboration Deployment (PCD) tool. If you are using PCD, you can perform a bulk installation of the COP files before you begin the upgrade.

You can download COP files for Cisco Unified Communications Manager and the IM and Presence Service at <https://software.cisco.com/download/home/268439621>. After you select the destination version for the upgrade, choose **Unified Communications Manager Utilities** to see the list of COP files.



**Note** You should run the Upgrade Readiness COP file prior to the upgrade in order to maximize upgrade success. If you do not run this COP file, you increase the risk of an unsuccessful upgrade due to undetected issues on the source release. Cisco TAC may require that you run this COP file to provide effective technical support.

**Table 2: Required COP Files**

From	To	COP Files
<b>Unified Communications Manager Upgrades</b>		

From	To	COP Files
Unified CM 10.5(x), 11.0(x)	12.5(x)	Direct Refresh upgrade Required COP file: ciscocm.enable-sha512sum-2021-signingkey-v1.0.cop.sgn. See the <a href="#">COP</a> file for more information.
Unified CM 11.5(x)	12.5(x)	Direct Refresh upgrade; COP file is required to increase the disk space.  <ul style="list-style-type: none"> <li>ciscocm.free_common_space_v&lt;latest_version&gt;.cop.sgn. To download the COP files and the Readme files, go to <a href="https://software.cisco.com">https://software.cisco.com</a>, click <b>Software Download</b> link under <b>Download &amp; Upgrade</b> section, and navigate to the <b>Unified Communications &gt; Call Control &gt; Cisco Unified Communications Manager (CallManager) &gt; &lt;Version&gt; &gt; Unified Communications Manager/CallManager/Cisco Unity Connection Utilities</b>.</li> </ul> Required COP file: ciscocm.enable-sha512sum-2021-signingkey-v1.0.cop.sgn. See the <a href="#">COP</a> file for more information.
Unified CM 12.0(1)	12.5(x)	PCD Migrations require a COP file:  <ul style="list-style-type: none"> <li>ciscocm-slm-migration.k3.cop.sgn</li> </ul> <b>Note</b> This requirement applies only for Prime Collaboration Deployment migrations from Release 12.0(1) of Unified Communications Manager (build 12.0.1.10000-10). If you are migrating from a higher release, such as Unified Communications Manager 12.0(1)SU1, you don't need to install the COP file.  Required COP file: ciscocm.enable-sha512sum-2021-signingkey-v1.0.cop.sgn. See the <a href="#">COP</a> file for more information.
Unified CM 12.5(x)	12.5(y)	Direct Standard upgrade Required COP file: ciscocm.enable-sha512sum-2021-signingkey-v1.0.cop.sgn. See the <a href="#">COP</a> file for more information.
<b>IM and Presence Service Upgrades</b>		
10.5(x), 11.x, 12.x	12.5(x)	No COP files required

## Supported Versions

The following table outlines which Unified Communications Manager and IM and Presence Service versions are supported with each release:

For this Release...	The Following Versions are Supported...
12.5(1)	<ul style="list-style-type: none"> <li>Unified Communications Manager 12.5.1.10000-22</li> <li>IM and Presence Service 12.5.1.10000-22</li> </ul>

<b>For this Release...</b>	<b>The Following Versions are Supported...</b>
12.5(1)SU1	<ul style="list-style-type: none"> <li>• Unified Communications Manager 12.5.1.11900-146</li> <li>• IM and Presence Service 12.5.1.11900-117</li> </ul>
12.5(1)SU2	<ul style="list-style-type: none"> <li>• Unified Communications Manager 12.5.1.12900-115</li> <li>• IM and Presence Service 12.5.1.12900-25</li> </ul>
12.5(1)SU3	<ul style="list-style-type: none"> <li>• Unified Communications Manager 12.5.1.13900-152</li> <li>• IM and Presence Service 12.5.1.13900-17</li> </ul>
12.5(1)SU4	<ul style="list-style-type: none"> <li>• Unified Communications Manager 12.5.1.14900-63</li> <li>• IM and Presence Service 12.5.1.14900-4</li> </ul>
12.5(1)SU5	<ul style="list-style-type: none"> <li>• Unified Communications Manager 12.5.1.15900-66</li> <li>• IM and Presence Service 12.5.1.15900-5</li> </ul>
12.5(1)SU6	<ul style="list-style-type: none"> <li>• Unified Communications Manager 12.5.1.16900-48</li> <li>• IM and Presence Service 12.5.1.16900-3</li> </ul>
12.5(1)SU7	<ul style="list-style-type: none"> <li>• Unified Communications Manager 12.5.1.17900-64</li> <li>• IM and Presence Service 12.5.1.17900-7</li> </ul>
12.5(1)SU7a	<ul style="list-style-type: none"> <li>• Unified Communications Manager 12.5.1.18100-14</li> <li>• IM and Presence Service 12.5.1.17900-7</li> </ul>
12.5(1)SU8	IM and Presence Service 12.5.1.18900-6
12.5(1)SU8a	Unified Communications Manager 12.5.1.18901-1

## **Version Compatibility Between Unified CM and the IM and Presence Service**

Version compatibility depends on the IM and Presence Service deployment type. The following table outlines the options and whether a release mismatch is supported between the telephony deployment and the IM and Presence Service deployment. A release mismatch, if it is supported, would let you deploy your Unified Communications Manager telephony deployment and your IM and Presence Service deployment using different releases.



**Note** Any respin or ES that is produced between [Cisco.com](https://www.cisco.com) releases is considered part of the previous release. For example, a Unified Communications Manager ES with a build number of 12.5.1.18[0-2]xx would be considered part of the 12.5(1)SU7 (12.5.1.17900-x) release.

For Release 12.5(1)SU7a, a Unified Communications Manager ES with a build number of 12.5.1.181xx would be considered part of the 12.5(1)SU7a (12.5.1.18100-x) release.

For Release 12.5(1)SU8a, a Unified Communications Manager ES with a build number of 12.5.1.19[0-2]xx would be considered part of the 12.5(1)SU8a (12.5.1.18901-1) release.

**Table 3: Version Compatibility between Unified Communications Manager and the IM and Presence Service**

Deployment Type	Release Mismatch	Description
Standard Deployment of IM and Presence Service	Not supported	Unified Communications Manager and the IM and Presence Service are in the same cluster and must run the same release—a release mismatch is not supported.
Centralized Deployment of IM and Presence Service	Supported	<p>The IM and Presence Service deployment and the telephony deployment are in different clusters and can run different releases—a release mismatch is supported.</p> <p><b>Note</b> The IM and Presence Service central cluster also includes a standalone Unified CM publisher node for database and user provisioning. This non-telephony node must run the same release as the IM and Presence Service.</p>

## Unified Communications Manager Compatibility Information

### Cisco Collaboration System Applications

The 12.5.x release of Cisco Unified Communications Manager and the IM and Presence Service is a part of the Cisco Collaboration Systems Release 12.5 through 12.8 and is compatible with the other Cisco Collaboration applications and versions in Cisco Collaboration Systems Release 12.5.



**Note** Note that Release 12.5(1)SU3 is compatible with the 12.8 version of the Cisco Collaboration Systems.

For a full list of Cisco Collaboration applications that are a part of Cisco Collaboration Systems Release 12.5(x), and the supported versions for each, see the *Cisco Collaboration Systems Release Compatibility Matrix* at: [https://www.cisco.com/c/dam/en/us/td/docs/voice\\_ip\\_comm/uc\\_system/unified/communications/system/Compatibility/CSR-Compatibility-Matrix-InteractiveHTML.html](https://www.cisco.com/c/dam/en/us/td/docs/voice_ip_comm/uc_system/unified/communications/system/Compatibility/CSR-Compatibility-Matrix-InteractiveHTML.html).

### Android Push Notifications Compatibility Recommendations

Android Push Notification feature is supported from the following software versions:

- Unified Communications Manager 12.5(1)SU3
- IM and Presence Service 12.5(1)SU3



- Cisco Jabber 12.9.1
- Cisco Expressway X12.6.2



**Note** This compatibility information isn't applicable for Cisco Webex.

**Table 4: Recommended Release Requirements for Android Push Notifications Support**

Unified Communications Manager and IM and Presence Service Version	Expressway Version	Unified Communications Mobile and Remote Access	On-Premises Deployments
All clusters on: <ul style="list-style-type: none"> <li>• 11.5(1)SU8 or earlier</li> <li>• 12.5(1)SU2 or earlier</li> </ul>	X12.6.2	Android Push Notification is not supported	Android Push Notification is not supported
All clusters on: <ul style="list-style-type: none"> <li>• 12.5(1)SU3 and onwards</li> </ul>	X12.6.2	Enable Android Push Notification using the CLI <b>xConfiguration XCP Config FcmService: On</b> on Expressway for messaging only	Android Push Notification is supported
Cluster with mixed versions (11.5(1)SU8 or earlier, OR 12.5(1)SU2 or earlier, AND 12.5(1)SU3 onwards)	X12.6.2	Android Push Notification for Messaging is not supported VOIP is supported from Release 12.5(1)SU3 onwards	Android Push Notification is supported from Release 12.5(1)SU3 onwards

### IM and Presence Stream Features/Services Advertisement Compatibility Recommendations

IM and Presence Service supports the advertisement of XMPP stream features/services to the clients connecting over Cisco Expressway's Mobile and Remote Access.

Depending on your current IM and Presence Service version mix, you may need to enable or disable push notifications feature using FCM service flag on the Expressway as per the information given in the following table:

`xConfiguration XCP Config FcmService: On/Off`



**Note** Apple Push Notification Service (APNS) is not affected by the FCM service flag status.

**Table 5: Solution Matrix from the Perspective of Expressway CLI Enable/Disable Command for Android Push Notifications (FCM)**

Mixed Versions IM and Presence Clusters	Expected Status of FCM Flag on Expressway X12.7	Comment
Any 11.5(1)SU with 12.5(1)SU2 and lower	OFF	Android Push (FCM) NOT supported.

Mixed Versions IM and Presence Clusters	Expected Status of FCM Flag on Expressway X12.7	Comment
11.5(1)SU8 (and lower) or 12.5(1)SU2 (and lower) with 12.5(1)SU3	OFF	Android push (FCM) NOT supported
11.5(1)SU8 (and lower) or 12.5(1)SU2 (and lower) with 12.5(1)SU4 (and higher)	OFF	Android push (FCM) supported on 12.5(1)SU4 (or newer) versions
11.5(1)SU9 (and higher) or 12.5(1)SU4 (and higher) with 12.5(1)SU3	ON	Android push (FCM) supported on version 12.5(1)SU3 and higher
11.5(1)SU9 (and higher) with 12.5(1)SU4 (and higher)	Flag not required (Expressway 12.7 relies fully on the new discovery mechanism)	Android push (FCM) supported on 12.5(1)SU4 (or newer) versions

## Cisco Endpoint Support

All end of Life and End of Sale announcements are listed here: <https://www.cisco.com/c/en/us/products/eos-eol-listing.html>.

### Supported Cisco Endpoints

The following table lists Cisco endpoints that are supported with this release of Cisco Unified Communications Manager. For endpoints that have reached End of Sale (EOS), or End of Software Maintenance, click the EOS link to view support details.



**Note** Unless they are specified in the "Deprecated Phone Models" list, phone models that are End of Software Maintenance will continue to be supported on the latest Unified Communications Manager releases. However, they will not take advantage of any new Unified Communications Manager or firmware features associated with that release.

**Table 6: Supported Cisco Endpoints**

Device Series	Device Model
Cisco Unified SIP Phone 3900 Series	Cisco Unified SIP Phone 3905
Cisco Unified IP Phone 6900 Series	Cisco Unified IP Phone 6901
Cisco IP Phone 7800 Series	Cisco IP Phone 7811 Cisco IP Phone 7821 Cisco IP Phone 7841 Cisco IP Phone 7861 Cisco IP Conference Phone 7832

Device Series	Device Model
Cisco Unified IP Phone 7900 Series	Cisco Unified IP Phone Expansion Module 7915— <a href="#">EOS Notice</a> Cisco Unified IP Phone Expansion Module 7916— <a href="#">EOS Notice</a> Cisco Unified IP Phone 7942G— <a href="#">EOS Notice</a> Cisco Unified IP Phone 7945G— <a href="#">EOS Notice</a> Cisco Unified IP Phone 7962G— <a href="#">EOS Notice</a> Cisco Unified IP Phone 7965G— <a href="#">EOS Notice</a> Cisco Unified IP Phone 7975G— <a href="#">EOS Notice</a>
Cisco IP Phone 8800 Series	Cisco IP Phone 8811, 8831, 8841, 8845, 8851, 8851NR, 8861, 8865, 8865NR Cisco Wireless IP Phone 8821, 8821-EX— <a href="#">EOL Notice</a> Cisco Unified IP Conference Phone 8831— <a href="#">EOS Notice</a> Cisco IP Conference Phone 8832 Cisco Video Phone 8875 Cisco Video Phone 8875NR
Cisco Unified IP Phone 8900 Series	Cisco Unified IP Phone 8945— <a href="#">EOS Notice</a> Cisco Unified IP Phone 8961— <a href="#">EOS Notice</a>
Cisco Unified IP Phone 9900 Series	Cisco Unified IP Phone 9951— <a href="#">EOS Notice</a> Cisco Unified IP Phone 9971— <a href="#">EOS Notice</a>
Cisco Jabber	Cisco Jabber for Android Cisco Jabber for iPhone and iPad Cisco Jabber for Mac Cisco Jabber for Windows Cisco Jabber Softphone for VDI - Windows (formerly Cisco Virtualization Experience Media Edition for Windows) Cisco Jabber Guest Cisco Jabber Software Development Kit Cisco Jabber for Tablet
Cisco Headset Series	Cisco Headset 320 Cisco Headset 520 Cisco Headset 530 Cisco Headset 560 Cisco Headset 720 Cisco Headset 730

<b>Device Series</b>	<b>Device Model</b>
Cisco IP Communicator	Cisco IP Communicator— <a href="#">EOS Notice</a>
Webex	Webex App Webex Room Phone Webex Desk Webex Desk Hub Webex Desk Pro Webex Desk Limited Edition Webex Share— <a href="#">EOS Notice</a> Board 55, 55S, 70, 70S, 85, 85S Webex Room Panorama Webex Room 70 Panorama Webex Room 70 Panorama Upgrade Room 70 Room 70 G2 Room 55 Room 55 Dual Room Kit Pro Room Kit Plus Room Kit Room Kit Mini Webex Room USB
Webex Wireless Phone 800 Series	Webex Wireless Phone 840 Webex Wireless Phone 860
Webex Meetings	Webex Meetings for iPad and iPhone Webex Meetings for Android
Cisco Analog Telephony Adapters	Cisco ATA 190 Series Analog Telephone Adapters— <a href="#">EOS/EOL Notice</a> Cisco ATA 191 Series Analog Telephone Adapters
Cisco DX Series	Cisco Webex DX70— <a href="#">EOS Notice</a> Cisco Webex DX80— <a href="#">EOS Notice</a> Cisco DX650— <a href="#">EOS Notice</a>
Cisco TelePresence IX5000	Cisco TelePresence IX5000
Cisco TelePresence EX Series	Cisco TelePresence System EX90— <a href="#">EOS Notice</a>

Device Series	Device Model
Cisco TelePresence MX Series	<a href="#">Cisco TelePresence MX200 G2—EOS Notice</a> <a href="#">Cisco TelePresence MX300 G2—EOS Notice</a> <a href="#">Cisco TelePresence MX700D—EOS Notice</a> <a href="#">Cisco TelePresence MX800S—EOS Notice</a> <a href="#">Cisco TelePresence MX800D—EOS Notice</a>
Cisco TelePresence SX Series	<a href="#">Cisco TelePresence SX10—EOS Notice</a> <a href="#">Cisco TelePresence SX20—EOS Notice</a> <a href="#">Cisco TelePresence SX80—EOS Notice</a>

Cisco Unified Communications Manager Release 12.5(1) is a part of Cisco Collaboration Systems Release 12.5. For a list of firmware versions that are used for each Cisco endpoint, see the *Cisco Collaboration Systems Release Compatibility Matrix* at [http://www.cisco.com/c/en/us/td/docs/voice\\_ip\\_comm/uc\\_system/unified/communications/system/Compatibility/CSR-Compatibility-Matrix.html](http://www.cisco.com/c/en/us/td/docs/voice_ip_comm/uc_system/unified/communications/system/Compatibility/CSR-Compatibility-Matrix.html).

For information about Device Pack compatibility to support the phones, see the *Cisco Unified Communications Manager Device Package Compatibility Matrix* at [http://www.cisco.com/c/en/us/td/docs/voice\\_ip\\_comm/cucm/compat/matrix/CMDP\\_BK\\_CCBDA741\\_00\\_cucm-device-package-compatibility-matrix.html](http://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/compat/matrix/CMDP_BK_CCBDA741_00_cucm-device-package-compatibility-matrix.html).

## End of Support

The following table lists Cisco endpoints that have reached the End of Support date, but which are not yet deprecated. Unlike deprecated endpoints, you can still deploy these endpoints in the latest release, but they are not supported actively, are not tested, and may not work.

Click the links to view support announcements for each endpoint.

For information on all of the End of Support and End-of-Life products, see [https://www.cisco.com/c/en\\_ca/products/eos-eol-listing.html](https://www.cisco.com/c/en_ca/products/eos-eol-listing.html).

**Table 7: Cisco Endpoints at End of Support**

Cisco Endpoints at End of Support
<ul style="list-style-type: none"> <li>• Cisco Unified SIP Phone <a href="#">3911</a>, <a href="#">3951</a></li> <li>• Cisco Unified IP Phone <a href="#">6911</a>, <a href="#">6921</a>, <a href="#">6941</a>, <a href="#">6945</a>, <a href="#">6961</a>, <a href="#">7906G</a>, <a href="#">7911G</a>, <a href="#">7931G</a>, <a href="#">7940G</a>, <a href="#">7941G</a>, <a href="#">7960G</a>, <a href="#">7961G</a>, <a href="#">8941</a></li> <li>• Cisco Unified IP Phone Expansion Module <a href="#">7925G</a>, <a href="#">7925G-EX</a>, <a href="#">7926G</a></li> <li>• Cisco Unified IP Conference Station <a href="#">7935</a>, <a href="#">7936</a>, <a href="#">7937G</a></li> <li>• Cisco TelePresence <a href="#">EX60</a></li> <li>• Cisco TelePresence <a href="#">MX200-G1</a>, <a href="#">MX200-G2</a>, <a href="#">MX300-G1</a>, <a href="#">MX300-G2</a></li> <li>• Cisco TelePresence <a href="#">500-32</a>, <a href="#">500-37</a>, <a href="#">1000 MXP</a>, <a href="#">1100</a>, <a href="#">1300-65</a>, <a href="#">1300-47</a>, <a href="#">3000 Series</a></li> </ul>

## Deprecated Phone Models

The following table lists all the phone models that are deprecated for this release of Unified Communications Manager, along with the Unified CM release where the phone model first became deprecated. For example, a phone model that was first deprecated in Release 11.5(1) is deprecated for all later releases, including all 12.x releases.

If you are upgrading to the current release of Unified Communications Manager and you have any of these phone models deployed, the phone will not work after the upgrade.

**Table 8: Deprecated Phone Models for this Release**

Deprecated Phone Models for this Release	First Deprecated as of Unified CM..
<ul style="list-style-type: none"> <li>• Cisco Unified Wireless IP Phone 7921</li> <li>• Cisco Unified IP Phone 7970</li> <li>• Cisco Unified IP Phone 7971</li> </ul>	12.0(1) and later releases
<ul style="list-style-type: none"> <li>• Cisco IP Phone 12 S</li> <li>• Cisco IP Phone 12 SP</li> <li>• Cisco IP Phone 12 SP+</li> <li>• Cisco IP Phone 30 SP+</li> <li>• Cisco IP Phone 30 VIP</li> <li>• Cisco Unified IP Phone 7902G</li> <li>• Cisco Unified IP Phone 7905G</li> <li>• Cisco Unified IP Phone 7910</li> <li>• Cisco Unified IP Phone 7910G</li> <li>• Cisco Unified IP Phone 7910+SW</li> <li>• Cisco Unified IP Phone 7910G+SW</li> <li>• Cisco Unified IP Phone 7912G</li> <li>• Cisco Unified Wireless IP Phone 7920</li> <li>• Cisco Unified IP Conference Station 7935</li> </ul>	11.5(1) and later releases

For additional information, refer to *Field Notice: Cisco Unified Communications Manager Release 11.5(x) does not support some deprecated phone models* at [https://www.cisco.com/c/en/us/td/docs/voice\\_ip\\_comm/cucm/rel\\_notes/11\\_5\\_1/fieldNotice/cucm\\_b\\_fn-deprecated-phone-models-1151.html](https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/rel_notes/11_5_1/fieldNotice/cucm_b_fn-deprecated-phone-models-1151.html).

For additional information refer to the Field Notice: *Cisco Unified Communications Manager Release 12.0(x) does not support some deprecated phone models* at [http://www.cisco.com/c/en/us/td/docs/voice\\_ip\\_comm/cucm/rel\\_notes/12\\_0\\_1/deprecated\\_phones/cucm\\_b\\_deprecated-phone-models-for-1201.html](http://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/rel_notes/12_0_1/deprecated_phones/cucm_b_deprecated-phone-models-for-1201.html).

## Upgrades that Involve Deprecated Phones

If you are using any of these phones on an earlier release and you want to upgrade to this release, do the following:

1. Confirm whether the phones in your network will be supported in this release.
2. Identify any non-supported phones.
3. For any non-supported phones, power down the phone and disconnect the phone from the network.
4. Provision a supported phone for the phone user. You can use the following methods to migrate from older model to newer model phones:
  - [Migration FX tool](#)
5. Once all the phones in your network are supported by this release, upgrade your system.




---

**Note** Deprecated phones can also be removed after the upgrade. When the administrator logs in to Unified Communications Manager after completing the upgrade, the system displays a warning message notifying the administrator of the deprecated phones.

---

### Licensing

You do not need to purchase a new device license to replace a deprecated phone with a supported phone. The device license becomes available for a new phone when you either remove the deprecated phone from the system, or when you switch to the new Unified Communications Manager version, and the deprecated phone fails to register.

## Virtualization Requirements

This release of Unified Communications Manager and the IM and Presence Service supports virtualized deployments only. Deployments on bare-metal servers are not supported. For more information, see <http://www.cisco.com/go/virtualized-collaboration>.

See the following table for virtualization requirements.

**Table 9: Virtualization Requirements**

Virtualization Requirements for...	For information, go to...
Unified Communications Manager	For information about Unified Communications Manager virtualization requirements, go to <a href="https://www.cisco.com/c/dam/en/us/td/docs/voice_ip_comm/uc_system/virtualization/virtualization-cisco-unified-communications-manager.html">https://www.cisco.com/c/dam/en/us/td/docs/voice_ip_comm/uc_system/virtualization/virtualization-cisco-unified-communications-manager.html</a> .
IM and Presence Service	For information about the IM and Presence Service virtualization requirements, go to <a href="https://www.cisco.com/c/dam/en/us/td/docs/voice_ip_comm/uc_system/virtualization/virtualization-cisco-ucm-im-presence.html">https://www.cisco.com/c/dam/en/us/td/docs/voice_ip_comm/uc_system/virtualization/virtualization-cisco-ucm-im-presence.html</a> .
Cisco Business Edition Deployments	For information on the virtualization requirements for Unified Communications Manager in a collaboration solution deployment such as Cisco Business Edition, go to <a href="https://www.cisco.com/c/dam/en/us/td/docs/voice_ip_comm/uc_system/virtualization/cisco-collaboration-infrastructure.html">https://www.cisco.com/c/dam/en/us/td/docs/voice_ip_comm/uc_system/virtualization/cisco-collaboration-infrastructure.html</a> .

## Supported LDAP Directories 12.5(x)

The following LDAP directories are supported:

- Microsoft Active Directory 2008 R1/ R2
- Microsoft Active Directory 2012 R1/ R2
- Microsoft Active Directory 2016
- Microsoft Active Directory 2019—Supported for 12.5(1)SU2 and later
- Microsoft Lightweight Directory Services 2008 R1/ R2
- Microsoft Lightweight Directory Services 2012 R1/ R2
- Microsoft Lightweight Directory Services 2019—Supported for 12.5(1)SU2 and later
- Oracle Directory Services Enterprise Edition 11gR1 (11.1.1.7.x or newer)
- Oracle Unified Directory 11gR2 (11.1.2.2.0 or 11.1.2.3.0)
- Open LDAP 2.4.45 or later
- Other LDAPv3 Compliant Directories—Unified Communications Manager uses standard LDAPv3 for accessing the user's data. Ensure that the supportedcontrol attribute is configured in the LDAPv3 compliant directory servers to be used with DirSync. (The supportedcontrol attribute may return the pagecontrolsupport and persistentcontrolsupport sub attributes, if configured.)

## Supported Web Browsers

The following web browsers are supported:

- Chrome with Windows 10 (64 bit)
- Firefox with Windows 10 (64 bit)
- Internet Explorer 11 with Windows 7 (64 bit)
- Internet Explorer 11 with Windows 10 (64 bit)
- Microsoft Edge browser with Windows 10 (32 bit/64 bit)
- Safari with MacOS (10.x)




---

**Note** We recommend that you use the latest version for all the web browsers supported.

---

## SFTP Server Support

For internal testing, we use the SFTP Server on Cisco Prime Collaboration Deployment (PCD) which is provided by Cisco, and which is supported by Cisco TAC. Refer to the following table for a summary of the SFTP server options:



**Table 10: SFTP Server Support**

SFTP Server	Support Description
SFTP Server on Cisco Prime Collaboration Deployment	<p>This server is the only SFTP server that is provided and tested by Cisco, and fully supported by Cisco TAC.</p> <p>Version compatibility depends on your version of Emergency Responder and Cisco Prime Collaboration Deployment. See the Cisco Prime Collaboration Deployment Administration Guide before you upgrade its version (SFTP) or Emergency Responder to ensure that the versions are compatible.</p>
SFTP Server from a Technology Partner	<p>These servers are third party provided and third party tested. Version compatibility depends on the third-party test. See the Technology Partner page if you upgrade their SFTP product and/or upgrade Unified Communications Manager for which versions are compatible:</p> <p><a href="https://marketplace.cisco.com">https://marketplace.cisco.com</a></p>
SFTP Server from another Third Party	<p>These servers are third party provided and are not officially supported by Cisco TAC. Version compatibility is on a best effort basis to establish compatible SFTP versions and Emergency Responder versions.</p> <p><b>Note</b> These products have not been tested by Cisco and we cannot guarantee functionality. Cisco TAC does not support these products. For a fully tested and supported SFTP solution, use Cisco Prime Collaboration Deployment or a Technology Partner.</p>

## SAML SSO Support

Although Cisco Collaboration infrastructure may prove to be compatible with other IdPs claiming SAML 2.0 compliance, only the following IdPs have been tested with Cisco Collaboration solutions:

- Microsoft® Active Directory® Federation Services 2.0, 3.0, 4.0, and 5.0
- Microsoft Azure AD
- Okta
- OpenAM
- PingFederate®
- F5 BIG-IP

For additional information on SAML SSO, see the *SAML SSO Deployment Guide for Cisco Unified Communications Applications*.

## API Development

The following table provides information on the API Development package that is supported with this release.

**Table 11: Supported API Package**

Package Type	Details
API Development	<p>Cisco Unified Communications Manager and the IM and Presence Service support OpenJDK for application development.</p> <ul style="list-style-type: none"><li>• Release 12.5(1) uses OpenJDK version 1.7.0.191.</li><li>• Release 12.5(1)SU1 uses OpenJDK version 1.7.0.201.</li><li>• Release 12.5(1)SU4 uses OpenJDK version 1.8.0.262.</li><li>• Release 12.5(1)SU5 uses OpenJDK version 1.8.0.262.</li><li>• Release 12.5(1)SU6 uses OpenJDK version 1.8.0.262.</li><li>• Release 12.5(1)SU7 uses OpenJDK version 1.8.0.262.</li><li>• Release 12.5(1)SU8 uses OpenJDK version 1.8.0.262.</li></ul>

## Secure Connections

### TLS 1.2 Support

Unified Communications Manager and the IM and Presence Service support the use of TLS 1.2. For detailed information on TLS 1.2 support, see the [TLS 1.2 Compatibility Matrix for Cisco Collaboration Products](#).

### SSL Connections

For Secure Sockets Layer (SSL) connections, this release supports both Cisco SSL and Cisco SSH:

- Cisco OpenSSL 1.0.2zf.6.2.511 and CiscoSSL 1.0.2zf.6.2.511
- Cisco OpenSSH client version 7.5.14i.1.5.18 and CiscoSSH 7.5.14i.1.5.18

## Supported Ciphers for Unified Communications Manager

The following ciphers are supported by Unified Communications Manager:

**Table 12: Unified Communications Manager Cipher Support for TLS Ciphers**

Application / Process	Protocol	Port	Supported Ciphers
Cisco CallManager	TCP / TLS	2443	<p>ECDHE-RSA-AES256-GCM-SHA384:                      ECDHE-RSA-AES256-SHA384:                      AES256-GCM-SHA384:                      AES256-SHA256:                      AES256-SHA:                      ECDHE-RSA-AES128-GCM-SHA256:                      ECDHE-RSA-AES128-SHA256:                      ECDHE-RSA-AES128-SHA:                      AES128-GCM-SHA256:                      AES128-SHA256:AES128-SHA:                      ECDHE-RSA-AES256-SHA:</p> <p><b>Note</b>           The following ciphers are not supported from Release 14SU2 onwards:</p> <p>CAMELLIA128-SHA                      CAMELLIA256-SHA:</p>
DRS	TCP / TLS	4040	<p>ECDHE-RSA-AES256-GCM-SHA384:                      ECDHE-RSA-AES256-SHA384:                      AES256-GCM-SHA384:AES256-SHA256:                      AES256-SHA:CAMELLIA256-SHA:                      ECDHE-RSA-AES128-GCM-SHA256:                      ECDHE-RSA-AES128-SHA256:                      ECDHE-RSA-AES128-SHA:                      AES128-GCM-SHA256:AES128-SHA256:                      AES128-SHA:                      ECDHE-RSA-AES256-SHA:                      DHE-RSA-CAMELLIA256-SHA:                      DHE-RSA-CAMELLIA128-SHA:                      CAMELLIA128-SHA</p>

Application / Process	Protocol	Port	Supported Ciphers
Cisco Tomcat	TCP / TLS	8443 / 443	<p> ECDHE-RSA-AES256-GCM-SHA384 :  ECDHE-RSA-AES256-SHA384 :  DHE-RSA-AES256-GCM-SHA384 :  DHE-RSA-AES256-SHA256 :  DHE-RSA-AES256-SHA :  AES256-GCM-SHA384 :AES256-SHA256 :  AES256-SHA :  ECDHE-RSA-AES128-GCM-SHA256 :  ECDHE-RSA-AES128-SHA256 :  ECDHE-RSA-AES128-SHA :  DHE-RSA-AES128-GCM-SHA256 :  DHE-RSA-AES128-SHA256 :  DHE-RSA-AES128-SHA :  AES128-GCM-SHA256 :AES128-SHA256 :  AES128-SHA :  ECDHE-ECDSA-AES256-GCM-SHA384 :  ECDHE-ECDSA-AES256-SHA384 :  ECDHE-ECDSA-AES256-SHA :  ECDHE-ECDSA-AES128-GCM-SHA256 :  ECDHE-ECDSA-AES128-SHA256 :  ECDHE-ECDSA-AES128-SHA :  ECDHE-RSA-AES256-SHA : </p> <p><b>Note</b>           The following ciphers are not supported from Release 14SU2 onwards:</p> <p> DHE-RSA-CAMELLIA256-SHA :  CAMELLIA256-SHA :  DHE-RSA-CAMELLIA128-SHA :  CAMELLIA128-SHA :  ECDHE-RSA-DES-CBC3-SHA :  EDH-RSA-DES-CBC3-SHA :  DES-CBC3-SHA :  ECDHE-ECDSA-DES-CBC3-SHA : </p>
Cisco CallManager	TCP / TLS	5061	<p> ECDHE-RSA-AES256-GCM-SHA384 :  ECDHE-ECDSA-AES256-GCM-SHA384 :  ECDHE-RSA-AES256-SHA384 :  ECDHE-ECDSA-AES256-SHA384 :  AES256-GCM-SHA384 :AES256-SHA256 :  AES256-SHA :  ECDHE-ECDSA-AES128-GCM-SHA256 :  ECDHE-RSA-AES128-GCM-SHA256 :  ECDHE-RSA-AES128-SHA256 :  ECDHE-ECDSA-AES128-SHA256 :  ECDHE-RSA-AES128-SHA :  ECDHE-ECDSA-AES128-SHA :  AES128-GCM-SHA256 :AES128-SHA256 :  AES128-SHA :  ECDHE-RSA-AES256-SHA : </p> <p><b>Note</b>           The following ciphers are not supported from Release 14SU2 onwards:</p> <p> ECDHE-ECDSA-AES256-SHA :  CAMELLIA256-SHA :  CAMELLIA128-SHA :  ECDHE-ECDSA-DES-CBC3-SHA : </p>

Application / Process	Protocol	Port	Supported Ciphers
Cisco CTL Provider <b>Note</b> Cisco CTL Provider is not available from Release 14SU3 onwards.	TCP / TLS	2444	AES256-GCM-SHA384:AES256-SHA256: AES256-SHA:CAMELLIA256-SHA: AES128-GCM-SHA256:AES128-SHA256: AES128-SHA:CAMELLIA128-SHA:
Cisco Certificate Authority Proxy Function	TCP / TLS	3804	AES256-GCM-SHA384:AES256-SHA256: AES256-SHA: AES128-GCM-SHA256:AES128-SHA256: AES128-SHA: <b>Note</b> The following ciphers are not supported from Release 14SU2 onwards: CAMELLIA256-SHA: CAMELLIA128-SHA:
CTIManager	TCP / TLS	2749	ECDHE-RSA-AES256-GCM-SHA384: ECDHE-RSA-AES256-SHA384: AES256-GCM-SHA384:AES256-SHA256: AES256-SHA: ECDHE-RSA-AES128-GCM-SHA256: ECDHE-RSA-AES128-SHA256: ECDHE-RSA-AES128-SHA: AES128-GCM-SHA256:AES128-SHA256: AES128-SHA: ECDHE-RSA-AES256-SHA: <b>Note</b> The following ciphers are not supported from Release 14SU2 onwards: CAMELLIA256-SHA: CAMELLIA128-SHA
Cisco Trust Verification Service	TCP / TLS	2445	AES256-GCM-SHA384:AES256-SHA256: AES256-SHA: AES128-GCM-SHA256:AES128-SHA256: AES128-SHA: <b>Note</b> The following ciphers are not supported from Release 14SU2 onwards: CAMELLIA256-SHA: CAMELLIA128-SHA

Application / Process	Protocol	Port	Supported Ciphers
Cisco Intercluster Lookup Service	TCP / TLS	7501	<p>ECDHE-RSA-AES256-GCM-SHA384:  ECDHE-RSA-AES256-SHA384:  AES256-GCM-SHA384:  AES256-SHA256:AES256-SHA:  ECDHE-RSA-AES128-GCM-SHA256:  ECDHE-RSA-AES128-SHA256:  ECDHE-RSA-AES128-SHA:  AES128-GCM-SHA256:AES128-SHA256:  AES128-SHA:  ECDHE-RSA-AES256-SHA:</p> <p><b>Note</b>           The following ciphers are not supported from Release 14SU2 onwards:</p> <p>CAMELLIA256-SHA:  CAMELLIA128-SHA:</p>
Secure Configuration download (HAPROXY)	TCP / TLS	6971, 6972	<p>ECDHE-RSA-AES256-GCM-SHA384:  ECDHE-RSA-AES256-SHA384:  AES256-GCM-SHA384:AES256-SHA256:  AES256-SHA:  ECDHE-RSA-AES128-GCM-SHA256:  ECDHE-RSA-AES128-SHA256:  ECDHE-RSA-AES128-SHA:  AES128-GCM-SHA256:AES128-SHA256:  AES128-SHA:  ECDHE-ECDSA-AES256-GCM-SHA384:  ECDHE-ECDSA-AES256-SHA384:  ECDHE-ECDSA-AES128-SHA256:  ECDHE-ECDSA-AES128-SHA:  ECDHE-RSA-AES256-SHA:</p> <p><b>Note</b>           The following ciphers are not supported from Release 14SU2 onwards:</p> <p>DHE-RSA-CAMELLIA256-SHA:  CAMELLIA256-SHA:  DHE-RSA-CAMELLIA128-SHA:  ECDHE-ECDSA-AES256-SHA:  ECDHE-ECDSA-DES-CBC3-SHA:  CAMELLIA128-SHA:</p>

Application / Process	Protocol	Port	Supported Ciphers
Authenticated Contact Search	TCP / TLS	9443	<p> ECDHE-RSA-AES256-GCM-SHA384:  ECDHE-RSA-AES256-SHA384:  AES256-GCM-SHA384:AES256-SHA256:  AES256-SHA:  ECDHE-RSA-AES128-GCM-SHA256:  ECDHE-RSA-AES128-SHA256:  ECDHE-RSA-AES128-SHA:  AES128-GCM-SHA256:AES128-SHA256:  AES128-SHA:  ECDHE-ECDSA-AES256-GCM-SHA384:  ECDHE-ECDSA-AES256-SHA384:  ECDHE-ECDSA-AES128-SHA256:  ECDHE-ECDSA-AES128-SHA:  ECDHE-RSA-AES256-SHA: </p> <p><b>Note</b>        The following ciphers are not supported from Release 14SU2 onwards:</p> <p> DHE-RSA-CAMELLIA256-SHA:  CAMELLIA256-SHA:  DHE-RSA-CAMELLIA128-SHA:  CAMELLIA128-SHA:  ECDHE-ECDSA-AES256-SHA:  ECDHE-ECDSA-DES-CBC3-SHA: </p>

## Supported Ciphers for SSH

The following ciphers are supported by SSH:

**Table 13: Cipher Support for SSH Ciphers**

Service	Ciphers/Algorithms
SSH Server	<ul style="list-style-type: none"> <li>• Ciphers <pre> aes128-ctr aes192-ctr aes256-ctr aes128-gcm@openssh.com aes256-gcm@openssh.com </pre> </li> <li>• MAC algorithms: <pre> hmac-sha2-256 hmac-sha2-512 hmac-sha1 </pre> </li> <li>• Kex algorithms: <pre> ecdh-sha2-nistp521 ecdh-sha2-nistp384 ecdh-sha2-nistp256 diffie-hellman-group14-sha1 diffie-hellman-group14-sha256 diffie-hellman-group16-sha512 </pre> </li> </ul>

Service	Ciphers/Algorithms
SSH Client	<ul style="list-style-type: none"> <li>• Ciphers: <ul style="list-style-type: none"> <li>aes128-ctr</li> <li>aes192-ctr</li> <li>aes256-ctr</li> <li>aes128-gcm@openssh.com</li> <li>aes256-gcm@openssh.com</li> </ul> </li> <li>• MAC algorithms: <ul style="list-style-type: none"> <li>hmac-sha2-256</li> <li>hmac-sha2-512</li> <li>hmac-sha1</li> </ul> </li> <li>• Kex algorithms: <ul style="list-style-type: none"> <li>ecdh-sha2-nistp521</li> <li>ecdh-sha2-nistp384</li> <li>ecdh-sha2-nistp256</li> <li>diffie-hellman-group14-sha1</li> <li>diffie-hellman-group14-sha256</li> <li>diffie-hellman-group16-sha512</li> </ul> </li> </ul>
DRS Client	<ul style="list-style-type: none"> <li>• Ciphers: <ul style="list-style-type: none"> <li>aes256-ctr</li> <li>aes256-cbc</li> <li>aes128-ctr</li> <li>aes128-cbc</li> <li>aes192-ctr</li> <li>aes192-cbc</li> </ul> </li> <li>• MAC algorithms: <ul style="list-style-type: none"> <li>hmac-md5</li> <li>hmac-sha2-256</li> <li>hmac-sha1</li> <li>hmac-sha1-96</li> <li>hmac-md5-96</li> </ul> </li> <li>• Kex algorithms: <ul style="list-style-type: none"> <li>ecdh-sha2-nistp256</li> <li>ecdh-sha2-nistp384</li> <li>ecdh-sha2-nistp521</li> <li>diffie-hellman-group14-sha1</li> <li>diffie-hellman-group-exchange-sha256</li> <li>diffie-hellman-group-exchange-sha1</li> <li>diffie-hellman-group1-sha1</li> </ul> </li> </ul> <p><b>Note</b>      The Kex algorithms diffie-hellman-group-exchange-sha256, diffie-hellman-group-exchange-sha1, and diffie-hellman-group1-sha1 are not supported from Release 12.5(1)SU4 if you have configured Cipher Management functionality in your Unified CM server. If the ciphers are not configured, DRS Client uses these algorithms.</p>



Service	Ciphers/Algorithms
SFTP client	<ul style="list-style-type: none"> <li>• Ciphers: <ul style="list-style-type: none"> <li>aes128-ctr</li> <li>aes192-ctr</li> <li>aes256-ctr</li> </ul> </li> <li>• MAC algorithms: <ul style="list-style-type: none"> <li>hmac-sha2-256</li> <li>hmac-sha1</li> </ul> </li> <li>• Kex algorithms: <ul style="list-style-type: none"> <li>ecdh-sha2-nistp521</li> <li>ecdh-sha2-nistp384</li> <li>diffie-hellman-group14-sha1</li> <li>diffie-hellman-group1-sha1</li> <li>diffie-hellman-group-exchange-sha256</li> <li>diffie-hellman-group-exchange-sha1</li> </ul> </li> </ul>
End Users	<ul style="list-style-type: none"> <li>hmac-sha512</li> <li>SHA-256 - Hashing (salted)</li> </ul>
DRS Backups / RTMT SFTPs	AES-128 - Encryption
Application Users	AES-256 - Encryption

## Supported Platforms for Cisco Unified JTAPI and TAPI

### Cisco Unified JTAPI

For a detailed breakdown of supported Windows, Linux, and VMware platforms for Cisco Unified JTAPI, see <https://developer.cisco.com/site/jtapi/documents/cisco-unified-jtapi-supported-jvm-versions/>.

For additional information that is related to Cisco Unified JTAPI, see *Cisco Unified JTAPI Developers Guide for Cisco Unified Communications Manager*.

### Cisco Unified TAPI

For a detailed breakdown of supported Windows platforms for Cisco Unified TAPI, see <https://developer.cisco.com/site/tapi/documents/supported-windows-os/>.

For additional information that is related to Cisco Unified TAPI, see *Cisco Unified TAPI Developers Guide for Cisco Unified Communications Manager*.

## IM and Presence Service Compatibility Information

### Platform Compatibility

The IM and Presence Service shares a platform with Unified Communications Manager. Many of the compatibility topics for Unified Communications Manager double as support topics for the IM and Presence Service. You can refer to the Unified Communications Manager compatibility chapter for information on the following items:

- Secure Connections
- Virtualization Requirements
- Supported Web Browsers

## External Database Support

Many IM and Presence Service features such as Persistent Chat, High Availability for Persistent Chat, Message Archiver, and Managed File Transfer require that you deploy an external database. For information on database support, see the [Database Setup Guide for the IM and Presence Service](#).

## Supported LDAP Directories 12.5(x)

The following LDAP directories are supported:

- Microsoft Active Directory 2008 R1/ R2
- Microsoft Active Directory 2012 R1/ R2
- Microsoft Active Directory 2016
- Microsoft Active Directory 2019—Supported for 12.5(1)SU2 and later
- Microsoft Lightweight Directory Services 2008 R1/ R2
- Microsoft Lightweight Directory Services 2012 R1/ R2
- Microsoft Lightweight Directory Services 2019—Supported for 12.5(1)SU2 and later
- Oracle Directory Services Enterprise Edition 11gR1 (11.1.1.7.x or newer)
- Oracle Unified Directory 11gR2 (11.1.2.2.0 or 11.1.2.3.0)
- Open LDAP 2.4.45 or later
- Other LDAPv3 Compliant Directories—Unified Communications Manager uses standard LDAPv3 for accessing the user's data. Ensure that the supportedcontrol attribute is configured in the LDAPv3 compliant directory servers to be used with DirSync. (The supportedcontrol attribute may return the pagecontrolsupport and persistentcontrolsupport sub attributes, if configured.)

## Federation Support

### SIP Federation/SIP Open Federation Support

SIP Open Federation is supported as of 12.5(1)SU3.

The following table lists supported SIP Controlled and SIP Open Federation integrations:

**Table 14: Supported SIP Controlled and Open Federations**

Third-Party System	Single Enterprise Network* (Intradomain or Interdomain Federation)		Business to Business (Interdomain Federation)
	Direct Federation	via Expressway	via Expressway
Skype for Business 2015 (on-premise)	Y	Not supported	Y (Traffic Classification)
Office 365 (uses a cloud-hosted Skype for Business)	Not applicable	Not applicable	Y (Traffic Classification)

\* The Single Enterprise Network can be partitioned intradomain federation or interdomain federation as the support values are the same for each. Business to Business integrations are always interdomain federation.

### Supported XMPP Federations

This release of IM and Presence Service supports XMPP Federation with the following systems:

- Cisco Webex Messenger
- IM and Presence Service Release 10.x and up
- Any other XMPP-compliant system

### Intercluster Peering Support

This release of the IM and Presence Service supports intercluster peering with the following IM and Presence Service releases:




---

**Note** Intercluster peering is not supported if the IM and Presence Service version has gone EOL/EOS.

---

- Release 11.x
- Release 12.x

### Calendar Integration with Microsoft Outlook

The IM and Presence Service supports Microsoft Outlook Calendar Integration with either an on-premise Exchange server or a hosted Office 365 server. See the table below for support information:




---

**Note** For technical support on any third-party products, contact the respective organization.

---

**Table 15: Support Information for Calendar Integration**

Component	Install Compatible Version
Windows Server	<ul style="list-style-type: none"> <li>• Service Packs for Windows Server 2012 (Standard)</li> <li>• Windows Server 2016</li> <li>• Windows Server 2019—With 11.x releases, the minimum IM and Presence Service Release is 11.5(1)SU7. With 12.x releases, the minimum IM and Presence Service Release is 12.5(1)SU2.</li> </ul>
Microsoft Exchange Server 2016	Microsoft Exchange 2016
Microsoft Exchange Server 2019	Microsoft Exchange 2019
Microsoft Office 365	<p>See your Microsoft documentation for details on deploying a hosted Office 365 server.</p> <p><b>Note</b> As of October 2020, Microsoft is changing the authentication mechanism that is supported by Exchange Online to use OAuth-based authentication only. After the change, if you want to deploy calendar integration between the IM and Presence Service and Office 365, you will need to upgrade the IM and Presence Service to Release 12.5(1)SU2. This change will not affect integration with an on-premises Exchange server.</p>
Active Directory	<ul style="list-style-type: none"> <li>• Active Directory 2012 with Windows Server 2012</li> <li>• Active Directory 2016 with Windows Server 2016</li> </ul> <p><b>Note</b> User names configured in Active Directory must be identical to those names defined in Unified Communications Manager.</p>
A Third-Party Certificate OR Certificate Server	<p>One or the other of these are required to generate the certificates.</p> <p><b>Note</b> Microsoft Exchange integration with IM and Presence Service supports certificates using RSA 1024 or 2048-bit keys and SHA1 and SHA256 signature algorithms.</p>

## Supported Ciphers for the IM and Presence Service

IM and Presence Service supports the following ciphers:

**Table 16: Unified Communications Manager IM & Presence Cipher Support for TLS Ciphers**

Application / Process	Protocol	Port	Supported Ciphers
Cisco SIP Proxy	TCP / TLS	5061	<p>                     ECDHE-RSA-AES256-GCM-SHA384 :                      ECDHE-ECDSA-AES256-GCM-SHA384 :                      ECDHE-RSA-AES256-SHA384 :                      ECDHE-ECDSA-AES256-SHA384 :                      AES256-GCM-SHA384 :AES256-SHA256 :                      AES256-SHA :                      ECDHE-RSA-AES128-GCM-SHA256 :                      ECDHE-ECDSA-AES128-GCM-SHA256 :                      ECDHE-RSA-AES128-SHA256 :                      ECDHE-ECDSA-AES128-SHA256 :                      ECDHE-RSA-AES128-SHA :                      ECDHE-ECDSA-AES128-SHA :                      AES128-GCM-SHA256 :                      AES128-SHA256 :                      AES128-SHA :                      ECDHE-RSA-AES256-SHA :                 </p> <p><b>Note</b>           The following ciphers are not supported from Release 14SU2 onwards:</p> <p>                     CAMELLIA256-SHA :                      CAMELLIA128-SHA :                      DES-CBC3-SHA :                      ECDHE-ECDSA-DES-CBC3-SHA :                      ECDHE-RSA-DES-CBC3-SHA :                      ECDHE-ECDSA-AES256-SHA :                 </p>
Cisco SIP Proxy	TCP / TLS	5062	<p>                     ECDHE-RSA-AES256-GCM-SHA384 :                      ECDHE-ECDSA-AES256-GCM-SHA384 :                      ECDHE-RSA-AES256-SHA384 :                      ECDHE-ECDSA-AES256-SHA384 :                      AES256-GCM-SHA384 :                      AES256-SHA256 :AES256-SHA :                      ECDHE-RSA-AES128-GCM-SHA256 :                      ECDHE-ECDSA-AES128-GCM-SHA256 :                      ECDHE-RSA-AES128-SHA256 :                      ECDHE-ECDSA-AES128-SHA256 :                      ECDHE-RSA-AES128-SHA :                      ECDHE-ECDSA-AES128-SHA :                      AES128-GCM-SHA256 :AES128-SHA256 :                      AES128-SHA :                      ECDHE-RSA-AES256-SHA :                 </p> <p><b>Note</b>           The following ciphers are not supported from Release 14SU2 onwards:</p> <p>                     CAMELLIA256-SHA :                      CAMELLIA128-SHA :                      DES-CBC3-SHA :                      ECDHE-ECDSA-DES-CBC3-SHA :                      ECDHE-RSA-DES-CBC3-SHA :                      ECDHE-ECDSA-AES256-SHA :                 </p>

Application / Process	Protocol	Port	Supported Ciphers
Cisco SIP Proxy	TCP / TLS	8083	<p> ECDHE-RSA-AES256-GCM-SHA384 :  ECDHE-ECDSA-AES256-GCM-SHA384 :  ECDHE-RSA-AES256-SHA384 :  ECDHE-ECDSA-AES256-SHA384 :  AES256-GCM-SHA384 :AES256-SHA256 :  AES256-SHA :  ECDHE-RSA-AES128-GCM-SHA256 :  ECDHE-ECDSA-AES128-GCM-SHA256 :  ECDHE-RSA-AES128-SHA256 :  ECDHE-ECDSA-AES128-SHA256 :  ECDHE-RSA-AES128-SHA :  ECDHE-ECDSA-AES128-SHA :  AES128-GCM-SHA256 :AES128-SHA256 :  AES128-SHA :  ECDHE-RSA-AES256-SHA :  </p> <p><b>Note</b>           The following ciphers are not supported from Release 14SU2 onwards:</p> <p> CAMELLIA256-SHA :  CAMELLIA128-SHA :  DES-CBC3-SHA :  ECDHE-ECDSA-DES-CBC3-SHA :  ECDHE-RSA-DES-CBC3-SHA :  ECDHE-ECDSA-AES256-SHA :  </p>
Cisco Tomcat	TCP / TLS	8443, 443	<p> ECDHE-RSA-AES256-GCM-SHA384 :  ECDHE-RSA-AES256-SHA384 :  DHE-RSA-AES256-GCM-SHA384 :  DHE-RSA-AES256-SHA256 :  DHE-RSA-AES256-SHA :  AES256-GCM-SHA384 :AES256-SHA256 :  AES256-SHA :  ECDHE-RSA-AES128-GCM-SHA256 :  ECDHE-RSA-AES128-SHA256 :  ECDHE-RSA-AES128-SHA :  DHE-RSA-AES128-GCM-SHA256 :  DHE-RSA-AES128-SHA256 :  DHE-RSA-AES128-SHA :  AES128-GCM-SHA256 :  AES128-SHA256 :AES128-SHA :  EDH-RSA-DES-CBC3-SHA :  ECDHE-ECDSA-AES256-GCM-SHA384 :  ECDHE-ECDSA-AES256-SHA384 :  ECDHE-ECDSA-AES128-GCM-SHA256 :  ECDHE-ECDSA-AES128-SHA256 :  ECDHE-ECDSA-AES128-SHA :  ECDHE-RSA-AES256-SHA :  </p> <p><b>Note</b>           The following ciphers are not supported from Release 14SU2 onwards:</p> <p> CAMELLIA128-SHA :  CAMELLIA256-SHA :  DES-CBC3-SHA :  ECDHE-ECDSA-DES-CBC3-SHA :  ECDHE-RSA-DES-CBC3-SHA :  DHE-RSA-CAMELLIA128-SHA :  DHE-RSA-CAMELLIA256-SHA :  ECDHE-ECDSA-AES256-SHA :  </p>

Application / Process	Protocol	Port	Supported Ciphers
Cisco XCP XMPP Federation Connection Manager	TCP / TLS	5269	<p> ECDHE-RSA-AES256-GCM-SHA384 :  ECDHE-ECDSA-AES256-GCM-SHA384 :  ECDHE-RSA-AES256-SHA384 :  ECDHE-ECDSA-AES256-SHA384 :  AES256-GCM-SHA384 :AES256-SHA256 :  AES256-SHA :  ECDHE-RSA-AES128-GCM-SHA256 :  ECDHE-ECDSA-AES128-GCM-SHA256 :  ECDHE-RSA-AES128-SHA256 :  ECDHE-ECDSA-AES128-SHA256 :  ECDHE-RSA-AES128-SHA :  ECDHE-ECDSA-AES128-SHA :  AES128-GCM-SHA256 :AES128-SHA256 :  AES128-SHA : </p> <p><b>Note</b>        The following ciphers are not supported from Release 14SU2 onwards:</p> <p> CAMELLIA256-SHA :  CAMELLIA128-SHA :  DES-CBC3-SHA :  ECDHE-ECDSA-DES-CBC3-SHA :  ECDHE-RSA-DES-CBC3-SHA :  ECDHE-ECDSA-AES256-SHA :  ECDHE-RSA-AES256-SHA : </p>
Cisco XCP Client Connection Manager	TCP / TLS	5222	<p> ECDHE-RSA-AES256-GCM-SHA384 :  ECDHE-ECDSA-AES256-GCM-SHA384 :  ECDHE-RSA-AES256-SHA384 :  ECDHE-ECDSA-AES256-SHA384 :  AES256-GCM-SHA384 :AES256-SHA256 :  AES256-SHA :  ECDHE-RSA-AES128-GCM-SHA256 :  ECDHE-ECDSA-AES128-GCM-SHA256 :  ECDHE-RSA-AES128-SHA256 :  ECDHE-ECDSA-AES128-SHA256 :  ECDHE-RSA-AES128-SHA :  ECDHE-ECDSA-AES128-SHA :  AES128-GCM-SHA256 :AES128-SHA256 :  AES128-SHA : </p> <p><b>Note</b>        The following ciphers are not supported from Release 14SU2 onwards:</p> <p> CAMELLIA128-SHA :  CAMELLIA256-SHA :  DES-CBC3-SHA :  ECDHE-ECDSA-DES-CBC3-SHA :  ECDHE-RSA-DES-CBC3-SHA :  ECDHE-ECDSA-AES256-SHA :  ECDHE-RSA-AES256-SHA : </p>

## Remote Call Control with Microsoft Lync

Microsoft Remote Call Control (RCC) allows enterprise users to control their Cisco Unified IP Phone or Cisco IP Communicator Phone through Microsoft Lync, a third-party desktop instant-messaging (IM) application. When a user signs in to the Microsoft Lync client, the Lync server sends instructions, through the IM and Presence Service node, to the Cisco Unified Communications Manager to set up, tear down and maintain calling features based on a user's action at the Lync client.



---

**Note** SIP federation and Remote Call Control (RCC) do not work together on the same IM and Presence Service cluster. This is because for SIP federation a user cannot be licensed for both Cisco IM and Presence Service and Microsoft Lync/OCS, but for RCC a user must be licensed for Cisco IM and Presence Service and Microsoft Lync/OCS at the same time.

---



---

**Note** An IM and Presence Service cluster that is used for RCC does not support Jabber or other IM and Presence Service functionality.

---

## Software Requirements

The following software is required for integrating IM and Presence Service with Microsoft Lync Server:

- IM and Presence Service, current release
- IM and Presence Service Lync Remote Call Control Plug-in
- Cisco Unified Communications Manager, current release
- Microsoft Lync Server 2013 Release 4.x, Standard Edition or Enterprise Edition
  - Lync Server Control Panel
  - Lync Server Deployment Wizard
  - Lync Server Logging Tool
  - Lync Server Management Shell
  - Lync Server Topology Builder
- Microsoft 2013 Lync Client
- (Optional) Upgraded Skype for Business 2015 Client



---

**Note** The Skype for Business 2015 client must have been upgraded from a Lync 2013 client and must be registered to a Lync 2013 server.

---

- (Optional) Cisco CSS 11500 Content Services Switch
- Microsoft Domain Controller
- Microsoft Active Directory
- DNS
- Certificate Authority



## **Configuration**

For additional details, including configuration information, see *Remote Call Control with Microsoft Lync Server for the IM and Presence Service* at <https://www.cisco.com/c/en/us/support/unified-communications/unified-presence/products-installation-and-configuration-guides-list.html>.





**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA 95134-1706  
USA

**Asia Pacific Headquarters**  
CiscoSystems(USA)Pte.Ltd.  
Singapore

**Europe Headquarters**  
CiscoSystemsInternationalBV  
Amsterdam,TheNetherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).